

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
7 March 2002 (07.03.2002)

PCT

(10) International Publication Number  
WO 02/19651 A2(51) International Patent Classification<sup>7</sup>: H04L 29/00

(21) International Application Number: PCT/US01/26456

(22) International Filing Date: 24 August 2001 (24.08.2001)

(25) Filing Language: English

(26) Publication Language: English


(30) Priority Data:  
60/228,128 25 August 2000 (25.08.2000) US  
09/870,959 30 May 2001 (30.05.2001) US(71) Applicant: FLATROCK, INCORPORATED [US/US];  
1505 S.E. Gideon, Suite 600, Portland, OR 97202 (US).(72) Inventors: BANKA, Peter, S.; 7941 SE 36th, Portland,  
OR 97202 (US). SILVERBERG, Sam, A.; 5831 NE Stan-  
ton, Portland, OR 97213 (US).(74) Agents: KLINDT WORTH, Jason, K. et al.; Columbia IP  
Law Group, PC, 4900 SW Meadows Road, Suite 109, Lake  
Oswego, OR 97035 (US).(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK,  
SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian  
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European  
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,  
IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,  
CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD,  
TG).

## Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for all designations
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR PROVIDING NETWORK DEPENDENT APPLICATION SERVICES



(57) Abstract: A method and apparatus for providing network dependent application services is provided. In accordance with one embodiment of the invention, a first group of one or more application service contracts specifying subscriptions to one or more application services are provided to a community of one or more subscriber application routers (SAR) by a first application service Provider. One or more application delivery transports are then automatically provisioned in accordance with the one or more application service contracts, and selected ones of the application services are delivered through selected ones of said application delivery transports.

WO 02/19651 A2

WO 02/19651 A2



**Published:**

— without international search report and to be republished  
upon receipt of that report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

# METHOD AND APPARATUS FOR PROVIDING NETWORK DEPENDENT APPLICATION SERVICES

## BACKGROUND OF THE INVENTION

### 1. Field of the Invention

The present invention relates to the field of computer networking. More specifically, the present invention relates to a method and apparatus for subscribing, authenticating, and provisioning network-based applications and services.

### 2. Background Information

With Internet usage becoming near ubiquitous, an ever-increasing number of software application providers and users are turning to the Internet for delivery of that software. Software vendors are migrating to an application service provider (ASP) model of software delivery, and corporate IT is beginning to look upon itself as an ASP, as a Provider to its own end user customers. The application service provider delivery model involves providing a set of one or more computer software applications or services through one or more network connections to a Subscriber, which obtains the application services from the Provider for the benefit of its end users.

In the past, the process of delivering applications from a Provider to a Subscriber (e.g. from an ASP to a Corporate Subscriber, or from Corporate IT to its end users) has been a manual, labor-intensive process as each Subscriber network or end user client was required to be manually configured in order to access each Provider network and Provider application. To accomplish this, Subscribers and Providers were often forced to undergo lengthy planning and design sessions, gathering information from Network/Internet service providers and application vendors for network and system integration.

Similarly in the past, Subscriber End User authentication has been performed on an application by application basis each time a user attempted to access an application hosted by the Provider. This required that the Subscriber notify the Provider and have the Provider update its authentication

databases every time the Subscriber required user access privileges to be changed. **Figure 1** illustrates a prior art Provider-Subscriber relationship whereby a Subscriber is connected (e.g., through Internet 105) to two Providers (Provider 1 & Provider 2) each hosting multiple applications. In the past, network integration between Providers and Subscribers has been prohibitively difficult, because of security policies enforced by firewalls and because of local network addressing requirements. To overcome these issues of connectivity, Providers and Subscribers have been forced to do one of two things: (1) pay for non-Internet Wide-Area-Network access through frame Relay, ATM, or private leased lines, or (2) go through the very expensive and time consuming process of installing a VPN solution. Each of these approaches are an expensive means of connecting the two organizations, and they do nothing to address the provisioning, authentication, allocation, and monitoring of the application to be delivered.

In the past it has been necessary for Subscriber End Users to be authenticated by the Provider prior to being granted access to the Provider's applications. For example, prior to being granted access to application "A", Subscriber End Users at clients 102-103 would be required to be authenticated via authentication database 107. To do so, clients 102-103 would transmit their user ID and password to Provider 1 where a comparison would be made against entries found in authentication database 107. Likewise, in order to access application "B", clients 102-103 would be required to be authenticated by way of authentication database 109, for example. Even in situations (as with Provider 2) where a single shared authentication database such as database 112 is utilized to authenticate Subscriber End Users for access to multiple Provider applications, the fact remains that the Provider maintains a complete set of user names, passwords, and group membership data independently of the Subscriber, thereby imposing significant administration requirements on the parts of both the Provider and the Subscriber, and forcing the Subscriber to give up control of sensitive information.

Therefore, what is needed is a scalable Subscriber-Provider model that overcomes the limitations of the prior art.

## BRIEF DESCRIPTION OF DRAWINGS

The present invention will be described by way of exemplary embodiments, but not limitations, illustrated in the accompanying drawings in which like references denote similar elements, and in which:

**Figure 1** is a block diagram illustrating a Provider-Subscriber relationship according to the prior art;

**Figure 2** is a block diagram illustrating various aspects of an application delivery network of the present invention;

**Figures 3A and 3B** together illustrate an operational flow diagram of various aspects of the contract creation process, in accordance with a passive Subscriber embodiment of the invention;

**Figure 4** illustrates an exemplary administrative interface for managing service Agreements at a PAR, in accordance with one embodiment of the invention;

**Figure 5** is an operational flow diagram illustrating relevant aspects of the contract fulfillment process of the present invention, in accordance with one embodiment;

**Figure 6** is an operational flow diagram illustrating aspects of the Subscriber End User authentication process of the present invention, in accordance with one embodiment;

**Figure 7**, is a block diagram illustrating a logical view of the application delivery network as it applies to one embodiment of the network address translation and encapsulation services of the present invention;

**Figures 8A and 8B** together graphically illustrate an operational flow of relevant aspects of the translation and encapsulation services of the present invention; and

**Figure 9** is a block diagram illustrating one embodiment of an application router of the present invention.

## DETAILED DESCRIPTION OF THE INVENTION

In the following description, various aspects of the present invention will be described. However, it will be apparent to those skilled in the art that the

present invention may be practiced with only some or all aspects of the present invention. For purposes of explanation, specific numbers, materials and configurations are set forth in order to provide a thorough understanding of the present invention. However, it will also be apparent to one skilled in the art that the present invention may be practiced without the specific details. In other instances, well-known features are omitted or simplified in order not to obscure the present invention.

Parts of the description will be presented in terms of operations performed by a processor based device, using terms such as data, tables, requesting, determining, retrieving, displaying, accessing, transmitting, and the like, consistent with the manner commonly employed by those skilled in the art to convey the substance of their work to others skilled in the art. As well understood by those skilled in the art, the quantities take the form of electrical, magnetic, or optical signals capable of being stored, transferred, combined, and otherwise manipulated through mechanical and electrical components of the processor based device; and the term processor include microprocessors, micro-controllers, digital signal processors, and the like, that are standalone, adjunct or embedded.

Various operations will be described as multiple discrete steps in turn, in a manner that is most helpful in understanding the present invention, however, the order of description should not be construed as to imply that these operations are necessarily order dependent. In particular, these operations need not be performed in the order of presentation. Further, the description repeatedly uses the phrase "in one embodiment", which ordinarily does not refer to the same embodiment, although it may.

### Overview

**Figure 2** is a block diagram illustrating various aspects of an application delivery network of the present invention. In **Figure 2**, a Subscriber Application Router (SAR) and a Provider Application Router (PAR), both incorporated with the teachings of the present invention, are shown. The SAR is coupled to Subscriber network 201, which interconnects client 202, client 204, optional domain name service (DNS) 206, and optional authentication authority 208. The

PAR on the other hand is coupled to provider network 215, which interconnects application server 214 hosting applications A and B, and application server 216 hosting applications C and D.

Subscriber network 201 is communicatively coupled to Provider network 215 via Subscriber firewall 209, networking fabric 205, and Provider firewall 219. Networking fabric 205 represents one or more interconnected data networks such as, but not limited to the Internet, whereas Subscriber network 201 and Provider network 215 each represent a network such as a local area network (LAN), campus network, or a multi-site WAN. In one embodiment, each site or campus is constrained to only one low-bandwidth WAN connection to an interconnected data network. Subscriber firewall 209 and Provider firewall 219 represent conventional routing devices designed to filter and route datagrams between local network domains and global network domains, as well as to conceal address information of the Subscriber or Provider network, as the case may be. For example, Subscriber firewall 209 routes datagrams between Subscriber network 201 and networking fabric 205, while optionally concealing the addresses of clients 204 and 205 from networking fabric 205. Similarly, Provider firewall 219 routes datagrams between provider network 215 and networking fabric 205 while optionally concealing the addresses of servers 214 and 216 from networking fabric 205.

In one embodiment, the SAR and the PAR are communicatively coupled through networking fabric 205 via transport 210. Transport 210 represents a virtual data path between globally addressable point GS of the Subscriber network and globally addressable point GP of the Provider network. In one embodiment, transport 210 represents a virtual private network ("VPN") comprising one or more tunnels provisioned between the Subscriber and the Provider to communicatively couple one or more SARs with one or more PARs.

In accordance with the teachings of the present invention, client 202 and/or client 204 access one or more applications from one or more Provider presentation servers (e.g. 214 and 216) via transport 210 in cooperation with the SAR and the PAR. In accordance with one embodiment of the invention, Subscriber authentication authority 208 authorizes client 202 and/or client 204 prior to client 202 and/or client 204 accessing the Provider's application. That is,

client 202 and/or client 204 can access the Provider's applications without the need for the Provider to necessarily maintain its own authentication database for each application.

In accordance with the teachings of the present invention, at least one of the PAR and the SAR is equipped with contract creation services (Provisioning), user authentication and authorization services (Allocation), and contract acceptance and connectivity establishment services (Fulfillment). Provisioning facilitates the creation of electronic service contracts (i.e. Agreements) between Subscribers and Providers. In one embodiment, each service contract represents a presentation method for a given application. In one embodiment contracts are implemented using a markup language, or an abstract syntax notation such as XML.

The Fulfillment services of the present invention facilitate automatic and transparent creation of one or more transports between the Subscriber network and the Provider network. In one embodiment, the establishment of the one or more transports is based at least in part upon terms of service agreed upon between the Subscriber and the Provider embodied in the form of one or more electronic service contracts. The Fulfillment services further operate to solicit and exchange, and maintain a history of operating characteristics, including bandwidth and quality of service (QOS) metrics pertaining to network connections between the Subscriber and the Provider, amongst a community of application routing devices disposed within the Provider and/or Subscriber networks. In one embodiment, a preferred network connection and corresponding application router is selected based upon the solicited operating characteristics to provide application services.

In one embodiment, the Fulfillment services of the present invention provide automatic and transparent datagram delivery between networks having diverse addressing requirements, including addresses spanning public and private (i.e. RFC 1918 or reserved RFC 1166 based) address spaces. In one embodiment, the fulfillment services include address translation and encapsulation services to translate local source and destination address pairs into virtual non-routable source and destination address pairs, which are then each encapsulated within a container packet and transmitted to a second



network via a pre-provisioned transport. Once received at the second network, the container packets are "unpackaged" to reveal the embedded virtual non-routable source and destination address pairs, which are further translated into a new source and destination address pair for delivery to the ultimate recipient while still implicitly identifying the original source. In one embodiment, a SAR transmits a container packet to a PAR identifying a subscriber client as the original source while identifying a Provider server as the ultimate recipient.

### **PAR Configuration**

Before a PAR is placed in communication with one or more SARs, the PAR is configured by e.g. a Provider administrator. More specifically, the PAR is provided with an appropriate subnet mask, default gateway and appropriate routing information (e.g. depending upon router/firewall presence or absence) as well as the network address of an external DNS server. In one embodiment, the Provider's own DNS server is configured to reference the PAR as a child domain for all application naming for which the Provider is authoritative (e.g. *apps.provider.com*) .

Each additional PAR that is added to the Provider domain and/or application delivery zone is likewise configured before becoming fully operational. In one embodiment, one or more PARs are designated as a "PAR Bridgehead." The PAR bridgehead accepts unsolicited connections from the Internet from new SARs that come online. The PAR Bridgehead verifies the authenticity of SARs and is responsible for making the SARs aware of any and all contracts that are available for Fulfillment. Moreover, the PAR Bridgehead functions as a "front door" to the Provider thereby reducing e.g. the negative impact of a Denial of Services attack from the Internet.

### **SAR Configuration**

As with PARs, SARs also involve minor initial configuration prior to becoming fully operational. To begin, an agent of the Subscriber provides the SAR with its own IP address information (e.g. the authorization to use a DHCP server or a combination of IP address, subnet mask, default gateway). Optionally, the SAR can be configured with network routing information that

allows the SAR to communicate to clients throughout the Subscriber's Internetwork. Next, the SAR is provided with the IP address or network name of a PAR Bridgehead. In one embodiment, the SAR is provided with a one-time password for initial communication with the PAR Bridgehead. Accordingly, the SAR performs an initial connection with the PAR Bridgehead using the provided one-time password to encrypt the traffic between the devices. Once communication is established with the PAR Bridgehead, public encryption keys are then exchanged between the Subscriber and Provider.

### Provisioning

In accordance with one aspect of the invention, a Subscriber enters into an electronic service Contract ("Contract") with a Provider to access (perhaps through lease or purchase) one or more applications and/or services hosted by the Provider. Each Contract between the Subscriber and the Provider (e.g. by way of one or more PARs) represents a particular presentation method for an application to be accessed by the Subscriber. That is, each Contract essentially represents a roadmap for providing a particular presentation service (e.g. application) to a subscriber, and may contain such items as payment terms, the number and nature of remote applications to be made accessible to the Subscriber, the number of licenses to be granted for each remote application, the number of virtual private network connections and/or tunnels to be provisioned between the Subscriber and the Provider, network security requirements of the application, client binary file distribution location and platform information, the bandwidth to be reserved for use by the Subscriber in accessing the remote applications, preferred performance and Quality of Service (QOS) levels, and so forth.

In one embodiment, termed an "Active Subscriber model," an agent of the Subscriber solicits an offer for service, including e.g. such terms as described above, from a Provider. In response, the Provider generates an electronic service Contract incorporating all, none, or only a portion of the terms solicited by the agent of the Subscriber. Once generated, the electronic service contract is transmitted by a PAR to a SAR for subsequent approval by an agent of the Subscriber. In one embodiment, the electronic service contract stipulating such

terms as described above is transmitted between PARs and SARs using an encrypted control channel. Once received, the Contract is reviewed and accepted by a designated agent of the Subscriber. The designated agent may be the agent of the Subscriber who originally solicited the offer, however, this need not be the case. For example, individuals such as a network administrator or groups of individuals such as a management committee responsible for purchasing may be designated as agents of the Subscriber for the purposes of the electronic service Contract.

In an alternative embodiment, the Subscriber is assumed to be "passive," allowing the Provider to stipulate the terms and conditions of the service Agreement autonomously. In such a "Passive Subscriber" embodiment, the SAR automatically approves the electronic service Contract without interaction from an agent of the Subscriber.

**Figures 3A and 3B** together illustrate an operational flow diagram of various aspects of the contract creation process, in accordance with a passive Subscriber embodiment of the invention. At block 302, an individual such as a Provider IT Administrator opens a user interface to a PAR (see e.g. **Figure 4**) in order to establish one or more Contracts for delivery to the Subscriber. Through the interface, the Provider selects applications to be provided to the Subscriber as well as corresponding presentation servers to provide the applications. The applications and corresponding presentation servers are then associated with the Contract at block 304. In one embodiment, the hostname of each participating presentation server is mapped to a contract ID for a particular application. Once created, the Contract is digitally signed by the PAR using the Provider's public key, and propagated to the remaining PARs (if any) at the Provider site, block 306.

The new Contract, and any other unapproved Contracts are then transmitted to the Subscriber for approval, along with a hash value representing all approved contracts that the PAR is aware of, block 308. In the passive Subscriber embodiment, the SAR automatically approves any unapproved contracts, whereas in an active Subscriber embodiment, an Agent of the Subscriber may choose to either approve or decline the contracts based upon

e.g. the terms of the Contracts. In one embodiment, the Subscriber's approval of the new Contract is established when a SAR has signed the Contract with its private key and has retransmitted the new Contract to the PAR Bridgehead. For the purposes of this description, it is assumed that the Subscriber has approved the Contracts and returned them back to the Provider, block 310. At this point, the PAR and the SAR each continue with the Fulfillment process independently from one another. The remainder of **Figure 3A** describes the SAR process for determining whether it is aware if all contracts yet to be fulfilled, whereas **Figure 3B** describes the Fulfillment process from the perspective of the PAR.

Continuing at block 312, the SAR determines whether the hash value received from the PAR (representing the list of approved contracts recognized by the PAR), matches a SAR hash value representing the approved contracts recognized by the SAR. If the respective hash values of the PAR and SAR indicate an approved contract status that differs from one another, the SAR downloads a complete list of approved contracts from the PAR, block 314. Finally, the SAR determines if there are any approved contracts that remain to be fulfilled, block 316, and if so, the SAR initiates Fulfillment (as described e.g. in **Figure 5**) for those Contracts, block 318. However, if there are no unfulfilled Contracts, the SAR again waits for new unapproved contract(s) from the Provider, block 308.

From the perspective of the PAR, once the SAR has returned the signed contracts to the PAR at block 310 of **Figure 3A**, the PAR verifies that the contract has not been tampered with and that the SAR has not rejected the agreement, block 320 of **Figure 3B**. The approved Contract is then circulated amongst all PARs, block 322. In one embodiment, each PAR, then attempts to connect to a predefined socket of a stipulated presentation server using a TCP port as indicated by the contract, block 324.

If a PAR is successful in connecting to the presentation server (block 326), the successful PAR registers itself with its PAR peers in a manner that indicates such, block 328. In one embodiment, this registration is done through DNS, where such a DNS entry may take on the following form: *contractID.apps.provider.com*, where "contractID" is an identifier (alphanumeric or otherwise) that identifies the particular contract

corresponding to the successful PAR service port connection to the Provider, and "apps.provider.com" represents the domain of the Provider network, or an application delivery zone within the domain. In one embodiment, a weight value is determined based upon the successful PAR's current processing and/or communication load. This weight value is used in load balancing and is made available to the PAR's peers. In one embodiment the weight value is stored in association with the DNS entry.

**Figure 4** illustrates an exemplary administrative interface for managing service Agreements at a PAR, in accordance with one embodiment of the invention. The administrative interface depicted in **Figure 4** includes application management controls 401, Subscriber Management controls 402, Server management controls 403, Contract Management controls 404, and an Add Contract dialog 406.

Application Management controls (401) provide the facility to describe the Provider's applications to the PARs. The information that may be entered here includes, for example, the name of the application, the default transport options, the icon that will appear on the Subscriber End User's desktop, and so forth.

Subscriber Management controls (402) provide the facility to describe the Subscribers that will be utilizing services from the Provider, while Server Management controls (403) provide the facility for maintaining the servers that will eventually service requests from the Subscriber.

Contract Management controls (404) provide the ability to create, edit, view, and delete contracts, whereas the Add Contract dialog (406) is the actual interface for creation of service Contracts. As shown, Add Contract dialog 406 provides for the synthesis of three pieces of data for the creation of a Contract: Subscriber, Application, and Server. Details of fulfillment (e.g. Encryption, Compression, Throttling, Monitored ports, Firewalled ports) can then be specified in the Contract.

It should be noted that the items depicted in **Figure 4** are merely intended to be illustrative and should not be read as limiting the invention. Furthermore, in an active Subscriber model, the service Agreement may be electronically

solicited from the Provider by the Subscriber rather than the Provider autonomously initiating the Agreement.

### Contract Fulfillment

#### PAR SELECTION

If a SAR identifies a contract that remains to be fulfilled (i.e. that does not have an active transport and is not yet available to clients), the SAR initiates a Contract Fulfillment process (e.g. block 318 of **Figure 3A**). **Figure 5** is an operational flow diagram illustrating relevant aspects of the Contract Fulfillment process in accordance with one embodiment of the invention. To begin, if it hasn't already done so, the SAR registers its own IP address and public key with the Provider, block 502. Using the Provider's public key, the SAR establishes an encrypted administrative channel with the PAR Bridgehead, and requests a list of PARs that have been identified as being able to support a given approved contract (i.e. able to connect via TCP to the presentation server(s) specified in the contract), block 504. In response, the PAR Bridgehead returns such a list to the SAR, block 506.

The SAR then probes PARs appearing in the list received from the Bridgehead to determine timing and performance metrics to ascertain each PAR's ability to service a particular Contract, block 508. In one embodiment of the invention, the SAR selects the PAR that proves to be the fastest. Through such an exchange, the SAR is able to achieve load balancing among multiple PARs at the Provider site, which assists in evening out the flow of datagrams transmitted over each tunnel thereby improving performance and availability.

Once a preferred PAR is identified (e.g. based upon the various timing and performance metrics), the SAR and preferred PAR negotiate a port, tunnel parameters, and a shared secret for a tunnel to be established, block 512. Additionally, the SAR and the PAR negotiate the addressing within the tunnel (see Transport Services below).

### Transport Services

Due to the blend of private and public addressing schemes that are typically encountered by a Subscriber and Provider while attempting to establish

connectivity to each other, the present invention includes network address translation and encapsulation ("Transport") services to facilitate transparent access by a client to an application and/or service hosted by a Provider. **Figure 7**, is a block diagram illustrating a logical view of an application delivery network as it applies to one embodiment of the Transport services of the present invention. Similarly, **Figures 8A and 8B** are block diagrams graphically illustrating an operational flow of relevant aspects of the Transport services of the present invention.

Reference is now made to **Figure 7**, where the application delivery network shown is similar in form to that illustrated in **Figure 2**. However, for the sake of clarity, the Subscriber and Provider firewalls have been omitted, and a logical tunnel network (710) has been shown. In the application delivery network of **Figure 7**, a Subscriber Application Router (SAR) and a Provider Application Router (PAR) both incorporated with the teachings of the present invention are shown. Subscriber network 701 interconnects the SAR with client 702, client 704, (optional) domain name service 706 and (optional) authentication authority 708. Provider network 715 interconnects the PAR with application server 714 hosting application "A", and application server 716 hosting application "B". In accordance with the teachings of the present invention, a client (e.g. client 702) of Subscriber network 701 accesses an application and/or service presented by Provider network 715 via one or more pre-provisioned transports between the SAR and the PAR, independent of each network's respective addressing scheme.

Referring now to **Figure 8A** with continuing reference made to **Figure 7**, the SAR (on network 701) is shown along with the path of a datagram traversing from Subscriber client 702, to the Provider's server hosting the requested application (after traversing the SAR, networking fabric 705, 701, and 715, and the PAR that is). To begin, it is assumed that Subscriber client 702 has selected (e.g., from a list) remote application "A" hosted by application server 714, which is coupled to the PAR on the Provider network. The datagram(s) sent from the client to access application "A" (i.e. signified as data) are created with the source address of X1 representing the Subscriber client 702 itself and a destination address of Y1 representing the local network address on the SAR.

In one embodiment, this local address for the SAR is obtained by the client from DNS (e.g. DNS 706 or DNS 717).

Upon being transmitted to and received by the SAR, the translation services of the SAR perform a lookup in table 802 to identify a virtual address pair that represents a (possibly encrypted, depending on terms of the contract) tunnel associated with application "A" and provisioned between the SAR and the PAR. In one embodiment, all source addresses of client computers are translated many-to-one to the same virtual source address within the tunnel, and all destination addresses are translated many-to-one to the same destination address within the tunnel. This is done for applications that handle network address translation without modification. In another embodiment, all source addresses of client and server computers are translated one-to-one. For example, because Subscriber client 702 initiated the request to virtual server address Y1 in the illustrated embodiment, based upon the data in table 802 the virtual address pair selected is Z1 and Z2 representing VPN tunnel 712 in **Figure 7**. However, if Subscriber client 704 had initiated the request to the same server Y1, table 802 would indicate a virtual address pair of Z3 and Z2 representing the same VPN tunnel. However, if Subscriber client 702 initiated the request to server 716 for application "B", the datagram would be sent, from address X1 to address Y2. The table 802 would, however, facilitate the translation of the source address to W1 and the destination address to W2, implying that the traffic should be sent through VPN 713 in **Figure 7**.

In the case of the client 702 sending from X1 to Y1, once the appropriate virtual address pair has been identified, Z1 is substituted for X1 and Z2 is substituted for Y1 in the datagram header (2B). Because the virtual address pairs are not routable (i.e. they utilize RFC 1918 or selected reserved RFC 1166 address space), the datagram is encapsulated within a second routable datagram in order to be transported over networking fabric 705. The second datagram is a routable IP-based datagram. To encapsulate the first datagram having virtual address pairs, a lookup is performed in table 804 by the SAR (3B). The datagram is encapsulated with globally addressable (and therefore routable) source and destination addresses based upon the virtual address pairs present in the first datagram. Because the SAR encapsulates the virtually



translated datagram within a globally-addressable second datagram, a wide variety of local addressing schemes and protocols may be utilized without negatively impacting the transparency of the data communications between the Subscriber network and the Provider. Once the datagram from Subscriber client 702 is encapsulated (4) the new datagram is delivered across networking fabric 705 towards the Provider as indicated by the destination address of the routable datagram. In one embodiment, the datagram is delivered across networking fabric 705 towards the Provider utilizing a pre-provisioned tunnel.

Referring now to **Figure 8B** with continuing reference to **Figure 7**, the PAR is shown along with the datagram of **Figure 8A** received through networking fabric 705 from the SAR on Subscriber network 701 (1). Upon being received by the PAR, the encapsulation service of the present invention "unpackages" the original datagram resulting in the datagram having the unroutable virtual address pairs (3). At this point, the "unpackaged " datagram is passed to the translation services of the invention (4A), whereby a lookup is performed in table 806 to determine the final source/destination address pair that identifies the requested application (4B). For example, because the virtual source/destination address pair is Z1 & Z2 in the illustrated embodiment, the translation services of the present invention substitute the P1 for the local (virtual client) source address and Q1 for the local destination address, resulting in the datagram being passed to application server 714 hosting application "A" just as if the datagram had originated at a client directly connected to network 715. In one embodiment, address P1 and Q1 are on the same subnet. Thus, it can be seen that with the transport services of the present invention, a datagram may be transparently delivered across networks employing a variety of addressing schemes without the need for inconvenient and time consuming manual configurations.

### **Tunnel Allocation**

When a SAR has selected a PAR that it wishes to communicate with, it will create the tunnel based on parameters in the Contract as well as dynamically negotiated parameters. In one embodiment, the following parameters are determined: shared secret for the tunnel, IP subnet address

within the tunnel, Virtual IP address of the client on the PAR, virtual IP address of the server on the SAR, encryption level, compression level, bandwidth throttling, monitored application ports, statefully monitored application ports, and the PAR's public IP address. In one embodiment, the PAR creates a tunnel process that listens for a connection from the SAR. When the SAR connects, the PAR sends an acknowledgement, and the PAR and the SAR then bind the tunnel parameters to a fully established tunnel.

In one embodiment, the virtual IP address of the Server on the SAR will be allocated from either a DHCP server on the Subscriber's network or from a pre-configured list that has been entered into the SAR. When the SAR has selected an IP address that will be used for the purpose of fulfilling this contract, that IP address will be transmitted to the PAR. The PAR will then publish that IP address to its local DNS process under the name of the contract ID. As the Provider references the PAR's DNS services as an authoritative subdomain, the DNS name for that contract will return the IP address of the SAR's allocated IP address for that contract. For example, if the provider is authoritative for the DNS domain "provider.com", and has designated a PAR as authoritative for "apps.provider.com", then the name "contractID.apps.provider.com" will resolve to the IP address that a SAR has allocated on the Subscriber's network.

### **Subscriber End User Allocation**

There are two aspects of Allocation. One is the ability for the present invention to restrict access to an application server through the network to only Subscriber end users that have been given rights to an application. The other, is the ability to determine the list of Subscriber End users that have been granted access to the server through the network and to make that list available to the Provider. The present invention uses two facilities to determine access for a given Subscriber End User: a Rulebase and an authentication authority. The Rulebase represents an internal list of rules that specify what user or group has access to what application under what circumstances. The authentication authority, however, is an external service that is maintained by the Subscriber and/or the Provider and allows the invention to determine (1) whether a given

username and password are authentic and (2) what users are contained within a group.

**Figure 6** is an operational flow diagram illustrating aspects of the Subscriber End User authentication process of the present invention, in accordance with one embodiment. Referring now back to **Figure 6**, a client establishes a data connection with a SAR logically disposed within the same Subscriber network as the client, block 602. A Subscriber End User of the client may initiate such contact with a SAR by selecting an icon displayed within a window or browser application executing upon the client, for example. In the "Active Subscriber" embodiment, if the Subscriber IT administrator has determined that authentication is necessary, the SAR requests a username and password from the Subscriber End User, block 604. Once obtained, the authentication credentials are validated against the Subscriber's authentication authority, such as an LDAP-compliant database, block 606. Once it is determined that the user has provided valid login credentials, the Rulebase is consulted to determine all applications for which the user has been authorized by e.g. the Subscriber IT Administrator.

Once the membership criteria is determined, the SAR notifies the authenticated Subscriber End user as to which such applications that user may access, block 608. That authenticated user may receive a graphical and/or alphanumeric notification depending upon the particular client implementation. At block 610, the authenticated Subscriber End user then selects one of the applications determined to be accessible.

Independent of whether the Subscriber IT Administrator (if one exists) has chosen to authenticate and authorize the Provider's applications to its users, the Provider may choose to authenticate the Subscriber End Users itself, block 612. For example, the SAR may have determined that a given Subscriber End User is allowed access to an application, but that user may be challenged (possibly again, if the SAR has already authenticated them) by the PAR if there are any applications that the Provider has specified as needing authentication. In one embodiment, the PAR will challenge any user that seeks to access an application that the PAR has designated as requiring authentication, block 614. This is achieved in the same manner as on the Subscriber side, except that the

Provider will challenge the Subscriber End User after they have received their list of applications and chooses to run one.

Determining a list of authorized Subscriber End Users is achieved through gathering user and group information from the authentication authority to determine all the users that are authorized by the Subscriber IT administrator to each of the Provider's applications, block 616. Independent of the login/authentication/authorization process, the SAR will periodically query the authentication authority against the local rulebase to determine a complete list of Subscriber end users that are authorized for each of the Provider's applications. The list of authorized users is then made available to the Provider Administrators, e.g. the administrator of the application and/or the authenticated client. In one embodiment, the list is made available via email, whereas in another embodiment the list is made available via an administration interface on the PAR(s).

The SAR then facilitates access (e.g. through Transport, described above) between their client and the selected Provider application, such as Applications "A" or "B", in response to such a selection by the Subscriber End User (block 618).

### **Exemplary Application Router**

**Figure 9** is a block diagram illustrating one embodiment of an application router of the present invention. Application router 900 includes network interfaces 910 and 910', processor 940, non-volatile memory 930 including network address translation tables 932 and contract profiles 934, and volatile memory 920 including the various services of the present invention, coupled together by way of bus 905. Network interfaces 910 and 910' include one or more ingress-egress packet buffers 912/912'.

Processor 940 represents one or more general purpose processors to execute instructions to cause application router 900 to process data packets in accordance with the teachings of the present invention. In other embodiments, processor 940 may instead represent one or more special purpose processors or application specific integrated circuits (ASICs). Volatile memory 920 represents any of the various readily available dynamic random access

memory devices, whereas non-volatile memory 930 represents any of the various readily available static random access memory devices. In accordance with the teachings of the present invention, volatile memory 920 includes Provisioning services 922, Allocation services 924, and Fulfillment services 926, as described herein above. Furthermore non-volatile memory 930 is shown to have contract profiles 934 and public/private key pairs for itself and public keys for any authorized PARs and SARs that this application router may communicate with (935).

While the present invention has been described in terms of the above illustrated embodiments, those skilled in the art will recognize that the invention is not limited to the embodiments described. The present invention can be practiced with modification and alteration within the spirit and scope of the appended claims. The description is thus to be regarded as illustrative instead of restrictive on the present invention.

---

1. A method comprising:
  - providing first one or more application service contracts by a first application service provider (Provider) to a community of one or more subscriber application routers (SAR), said first one or more application service contracts specifying subscriptions to first one or more application services provided by first one or more servers of said first Provider;
  - automatically provisioning first one or more application delivery transports to facilitate delivery of said first one or more application services provided by said first one or more servers of said first Provider to clients of said Subscriber in accordance with said first one or more application service contracts;
  - providing second one or more application service contracts by a second application service provider (Provider) to the community of one or more subscriber application routers (SAR), said second one or more application service contracts specifying subscriptions to second one or more application services provided by second one or more servers of said second Provider;
  - automatically provisioning second one or more application delivery transports to facilitate delivery of said second one or more application services provided by said second one or more servers of said second Provider to clients of said Subscriber in accordance with said second one or more application service contracts; and
  - delivering selected ones of said first and second application services provided by said first and second one or more servers of said first and second Providers through selected ones of said first and second application delivery transports respectively.
2. The method of claim 1, wherein said first one or more application service contracts are provided by a community of one or more provider application routers (PARs) and said second one or more application service contracts are provided by a second community of one or more PARs.
3. The method of claim 2, wherein said automatically provisioning first one or more application delivery transports further comprises:

identifying, by a first SAR of said community of one or more SARs, a preferred PAR of said first community of one or more PARs; and

negotiating a subnet and a shared secret between said first SAR and said preferred PAR to facilitate provisioning of said first one or more delivery transports.

4. The method of claim 1, wherein said providing first one or more application service contracts to a community of one or more SAR(s) comprises providing one or more unapproved service contracts to a community of one or more SAR(s) for approval by the SAR(s).

5. The method of claim 4, wherein said community of one or more SAR(s) approves said one or more unapproved service contracts through manifestation of a digital signature by the approving SAR(s).

6. The method of claim 1, wherein at least one of said first one or more application delivery transports and said second one or more application delivery transports comprise one or more virtual private network tunnels.

7. In a subscriber application routing device (SAR), a method comprising:

receiving first one or more application service contracts from a first application service provider (Provider), said first one or more application service contracts specifying subscriptions to first one or more application services provided by first one or more servers of said first Provider;

automatically provisioning first one or more application delivery transports to facilitate delivery of said first one or more application services provided by said first one or more servers of said first Provider to clients of said Subscriber in accordance with said first one or more application service contracts;

receiving second one or more application service contracts from a second application service provider (Provider), said second one or more application service contracts specifying subscriptions to second one or more application services provided by second one or more servers of said second provider;

automatically provisioning second one or more application delivery transports to facilitate delivery of said second one or more application services

provided by said second one or more servers of said second Provider to clients of said Subscriber in accordance with said second one or more application service contracts; and

receiving selected ones of said first and second application services provided by said first and second one or more servers of said first and second Providers through selected ones of said first and second application delivery transports.

8. The method of claim 7, wherein said SAR solicits said first one or more application service contracts from said first provider.
9. The method of claim 7, wherein said first one or more application service contracts are received from said first provider through an encrypted control channel.
10. The method of claim 7, further comprising:
  - approving at least a subset of said first one or more application service contracts received from said first provider, and
  - transmitting said approved one or more application service contracts back to said first provider.
11. The method of claim 7, wherein said automatically provisioning said first one or more application delivery transports comprises automatically provisioning a first one or more virtual private network tunnels between said SAR and said first provider.
12. A subscriber application routing device (SAR) comprising:
  - a storage medium having stored therein a plurality of programming instructions, which when executed cause the SAR to
    - receive first one or more application service contracts from a first application service provider (Provider), said first one or more application service contracts specifying subscriptions to first one or more application services provided by first one or more servers of said first Provider,
    - automatically provision first one or more application delivery transports to facilitate delivery of said first one or more application services provided by said first one or more servers of said first Provider



to clients of said Subscriber in accordance with said first one or more application service contracts,

receive second one or more application service contracts from a second application service provider (Provider), said second one or more application service contracts specifying subscriptions to second one or more application services provided by second one or more servers of said second provider,

automatically provision second one or more application delivery transports to facilitate delivery of said second one or more application services provided by said second one or more servers of said second Provider to clients of said Subscriber in accordance with said second one or more application service contracts, and

receive selected ones of said first and second application services provided by said first and second one or more servers of said first and second Providers through selected ones of said first and second application delivery transports; and

an execution unit coupled to the storage medium for executing the plurality of programming instructions.

13. The SAR of claim 12, wherein said SAR solicits said first one or more application service contracts from said first provider.

14. The SAR of claim 12, wherein said first one or more application service contracts are received from said first provider through an encrypted control channel.

15. The SAR of claim 12, further comprising instructions to

approve at least a subset of said first one or more application service contracts received from said first provider, and

transmit said approved one or more application service contracts back to said first provider.

16. The SAR of claim 12, wherein said instructions to automatically provision said first one or more application delivery transports further comprises instructions to automatically provision a first one or more virtual private network tunnels between said SAR and said first provider.

17. In a subscriber application routing device (SAR), a method comprising:  
receiving one or more application service contracts from an application service provider (Provider), said one or more application service contracts specifying subscriptions to one or more application services provided by one or more servers of said Provider;  
request from the Provider a list of provider application routers (PARs) identified as being able to support a given contract of said one or more application service contracts;  
automatically provisioning one or more application delivery transports between said SAR and a selected one or more of said listed PARs to facilitate delivery of said one or more application services provided by said one or more servers of said Provider to clients of said Subscriber in accordance with said one or more application service contracts; and  
receiving selected ones of said application services provided by said one or more servers of said Provider through selected ones of said application delivery transports respectively.
18. A subscriber application routing device (SAR) comprising:  
a storage medium having stored therein a plurality of programming instructions, which when executed cause the SAR to  
receive one or more application service contracts from an application service provider (Provider), said one or more application service contracts specifying subscriptions to one or more application services provided by one or more servers of said Provider,  
request from the Provider a list of provider application routers (PARs) able to support a given contract of said one or more application service contracts;  
automatically provision one or more application delivery transports between said SAR and a selected one or more of said listed PARs to facilitate delivery of said one or more application services provided by said one or more servers of said Provider to clients of said Subscriber in accordance with said one or more application service contracts,

receive selected ones of said application services provided by said one or more servers of said Provider through selected ones of said application delivery transports respectively; and an execution unit coupled to the storage medium for executing the plurality of programming instructions.

19. In a provider application routing device (PAR), a method comprising: providing first one or more application service contracts to a first community of one or more subscriber application routers (SAR), said first one or more application service contracts specifying subscriptions to first one or more application services provided by first one or more servers of said Provider;

providing second one or more application service contracts to a second community of one or more subscriber application routers (SAR), said second one or more application service contracts specifying subscriptions to second one or more application services provided by second one or more servers of said Provider; and

delivering selected ones of said first and second application services provided by said first and second one or more servers of said Provider through selected ones of a first one or more application delivery transports provisioned between said first community of one or more SARs and said PAR and a second one or more application delivery transports provisioned between said second community of one or more SARs and said PAR.

20. The method of claim 19, wherein the selected ones of said first and second application services are delivered to one or more clients of said first community of one or more SARs.

21. The method of claim 19, wherein said PAR is one of a community of PARs.

22. The method of claim 21, further comprising:

identifying which PAR(s) amongst the community of PARs are able to support a selected one of said first one or more application service contracts; and

notifying said first community of one or more SARs as to which PARs are able to support the selected one of said first one or more application service contracts.

23. The method of claim 19, wherein said first one or more application delivery transports comprise first one or more virtual private network tunnels.

24. A provider application routing device (PAR) comprising:

a storage medium having stored therein a plurality of programming instructions, which when executed cause the PAR to

provide first one or more application service contracts to a first community of one or more subscriber application routers (SAR), said first one or more application service contracts specifying subscriptions to first one or more application services provided by first one or more servers of said Provider,

provide second one or more application service contracts to a second community of one or more subscriber application routers (SAR), said second one or more application service contracts specifying subscriptions to second one or more application services provided by second one or more servers of said Provider, and

deliver selected ones of said first and second application services provided by said first and second one or more servers of said Provider through selected ones of a first one or more application delivery transports provisioned by said first community of one or more SARs and a second one or more application delivery transports provisioned by said second community of one or more SARs; and

an execution unit coupled to the storage medium for executing the plurality of programming instructions.

25. The PAR of claim 24, wherein the selected ones of said first and second application services are delivered to one or more clients of said first community of one or more SARs.

26. The PAR of claim 24, wherein said PAR is one of a community of PARs.

27. The PAR of claim 26, further comprising instructions to:

identify which PAR(s) amongst the community of PARs are able to support a selected one of said first one or more application service contracts; and

notify said first community of one or more SARs as to which PARs are able to support the selected one of said first one or more application service contracts.

28. The PAR of claim 24, wherein said first one or more application delivery transports comprise first one or more virtual private network tunnels.

29. In a subscriber application routing apparatus (SAR), a method comprising:

receiving an application service contract from an application service provider (Provider) specifying subscriptions to one or more application services to be provided by one or more servers of said Provider;

obtaining networking performance metrics from one or more provider application routing apparatuses (PARs);

selecting one of said one or more PARs to facilitate provision of said one or more application services based at least in part upon said performance metrics; and

automatically provisioning one or more application delivery transports between said Subscriber and said selected PAR to facilitate delivery of said one or more application services to be provided by said one or more servers of said Provider to clients of said Subscriber.

30. The method of claim 29, further comprising:

receiving from the Provider, a list of said one or more PARs determined to be equipped to facilitate provision of said one or more application services.

31. The method of claim 30, wherein said one or more PARs belong to a larger community of PARs including PARs not equipped to facilitate provision of said one or more application services to said subscriber.

32. The method of claim 30, wherein said networking performance metrics are obtained from said one or more PARs determined to be equipped to facilitate provision of said one or more application services.

33. The method of claim 30, wherein said selecting one of said one or more PARs to facilitate provision of said one or more application services comprises selecting a single PAR having a fastest response time amongst said one or more PARs.
34. The method of claim 29, wherein automatically provisioning further comprises:
- negotiating a subnet and a shared secret between said SAR and said selected PAR to facilitate provisioning of said first one or more delivery transports.
35. The method of claim 34, wherein said one or more delivery transports comprise one or more virtual private network tunnels.
36. An application routing apparatus (SAR) comprising:
- a storage medium having stored therein a plurality of programming instructions, which when executed cause the apparatus to
    - receive an application service contract from an application service provider (Provider) specifying subscriptions to one or more application services to be provided by one or more servers of said Provider,
    - obtain networking performance metrics from one or more provider application routing apparatuses (PARs),
    - select one of said one or more PARs to facilitate provision of said one or more application services based at least in part upon said performance metrics, and
    - automatically provision one or more application delivery transports between said Subscriber and said selected PAR to facilitate delivery of said one or more application services to be provided by said one or more servers of said Provider to clients of said Subscriber; and
  - an execution unit coupled to the storage medium for executing the plurality of programming instructions.
37. The apparatus of claim 36, wherein said plurality of programming instructions further comprise instructions to:
- receive from the Provider, a list of said one or more PARs determined to be equipped to facilitate provision of said one or more application services.

38. The apparatus of claim 37, wherein said one or more PARs belong to a larger community of PARs including PARs not equipped to facilitate provision of said one or more application services to said Subscriber.

39. The apparatus of claim 37, wherein said networking performance metrics are obtained from said one or more PARs determined to be equipped to facilitate provision of said one or more application services.

40. The apparatus of claim 37, wherein said plurality of programming instructions to select one of said one or more PARs to facilitate provision of said one or more application services further comprises instructions to select a single PAR having a fastest response time amongst said one or more PARs.

41. The apparatus of claim 36, wherein said plurality of programming instructions to automatically provision further comprises instructions to negotiate a subnet and a shared secret between said SAR and said selected PAR to facilitate provisioning of said first one or more delivery transports.

42. The apparatus of claim 41, wherein said one or more delivery transports comprise one or more virtual private network tunnels.

43. In a Provider application routing apparatus (PAR), a method comprising:  
delivering an application service contract to an application service subscriber (Subscriber) specifying subscriptions to one or more application services to be provided by one or more servers of said Provider;

receiving from said subscriber, a manifestation of approval to said application service contract;

determining which one or more PARs amongst a community of one or more PARs is equipped to facilitate provisioning of said one or more application services; and

automatically provisioning one or more application delivery transports between said Subscriber and a selected one or more of said PARs equipped to facilitate delivery of said one or more application services to be provided by said one or more servers of said Provider to clients of said Subscriber.

44. The method of claim 43, wherein receiving said manifestation includes receiving a digitally signed version of said application service contract.
45. The method of claim 44, further comprising circulating said digitally signed version of said application service contract amongst said community of one or more PARs.
46. The method of claim 45, further comprising verifying at least one of non-repudiation and authenticity of said received digitally signed version of said application service contract.
47. The method of claim 46, wherein determining which one or more PARs amongst a community of one or more PARs is equipped to facilitate provisioning of said one or more application services further comprises each PAR of said community of one or more PARs attempting to connect to at least one of said one or more servers of said Provider.
48. The method of claim 47, wherein attempting to connect further comprises each PAR of said community of one or more PARs attempting to connect to a predefined socket of a server indicated by said application service contract.
49. The method of claim 43, wherein said selected one or more of said PARs are selected by said Subscriber.
50. The method of claim 43, wherein said one or more delivery transports comprise one or more virtual private network tunnels.
51. A Provider application routing apparatus (PAR) comprising:  
a storage medium having stored therein a plurality of programming instructions, which when executed cause the apparatus to  
deliver an application service contract to an application service subscriber (Subscriber) specifying subscriptions to one or more application services to be provided by one or more servers of said Provider,  
receive from said subscriber, a manifestation of approval to said application service contract,



determine which one or more PARs amongst a community of one or more PARs is equipped to facilitate provisioning of said one or more application services, and

automatically provision one or more application delivery transports between said Subscriber and a selected one or more of said PARs equipped to facilitate delivery of said one or more application services to be provided by said one or more servers of said Provider to clients of said Subscriber; and

an execution unit coupled to the storage medium for executing the plurality of programming instructions.

52. The apparatus of claim 51, wherein said plurality of programming instructions to receive said manifestation further comprises instructions to receive a digitally signed version of said application service contract.

53. The apparatus of claim 52, wherein said plurality of programming instructions further comprise instructions to circulate said digitally signed version of said application service contract amongst said community of one or more PARs.

54. The apparatus of claim 53, wherein said plurality of programming instructions further comprise instructions to verify at least one of non-repudiation and authenticity of said received digitally signed version of said application service contract.

55. The apparatus of claim 54, wherein said plurality of programming instructions to determine which one or more PARs amongst a community of one or more PARs is equipped to facilitate provisioning of said one or more application services further comprises instructions to cause each PAR of said community of one or more PARs to attempt to connect to at least one of said one or more servers of said Provider.

56. The apparatus of claim 55, wherein said plurality of programming instructions to cause each PAR of said community of one or more PARs to attempt to connect to at least one of said one or more servers of said Provider further comprises instructions to cause each PAR of said community of one or

more PARs to attempt to connect to a predefined socket of a server indicated by said application service contract.

57. The apparatus of claim 51, wherein said selected one or more of said PARs are selected by said Subscriber.

58. The apparatus of claim 51, wherein said one or more delivery transports comprise one or more virtual private network tunnels.

59. A method comprising:

a client of an application service subscriber (Subscriber) transmitting a packet to an application routing apparatus of the Subscriber (SAR), the packet to be delivered to an application service hosted by a server of an application service provider (Provider) and employing a first source and destination address pair having a first source address that identifies the client as the source of the packet and a first destination address identifying the SAR as an immediate intermediate recipient of the packet, with the first destination address further identifying an application routing apparatus of the Provider (PAR);

the SAR transforming the packet for forwarding to said server, including transforming the first source and destination addresses to second source and destination addresses with the second source address identifying the SAR as the source of the packet and the second destination address identifying the PAR as the recipient of the transformed packet, the second source address also identifying the client as the original source of the transformed packet and the second destination address also identifying the server as the ultimate destination of the transformed packet;

the SAR embedding the transformed packet as a payload of a container packet and transmitting the container packet to the PAR employing a third source and destination address pair identifying the SAR and the PAR as the respective source and destination of the container packet;

the PAR extracting the embedded payload and further transforming the extracted payload as a twice transformed packet, said transforming including the PAR transforming said second source and destination addresses to fourth source and destination addresses, with the fourth source and destination

addresses identifying the PAR and the server as the respective source and destination of the twice transformed packet, the fourth source address further identifying the client as the original source of the twice transformed packet; and the PAR transmitting the twice transformed packet to the server to facilitate delivery of said application service.

60. The method of claim 59, wherein the first destination address identifying the SAR as an immediate intermediate recipient of the packet is obtained from a domain name service.

61. The method of claim 59, wherein the SAR transforming the packet further comprises:

performing a lookup to identify the second source and destination addresses, said second source and destination addresses together representing a virtual private network tunnel provisioned between said SAR and PAR and associated with said application service.

62. The method of claim 59, wherein the second source and destination addresses represent a virtual address pair including a non-routable virtual source address and a non-routable virtual destination address.

63. The method of claim 62, wherein said virtual source address corresponds to a plurality of client source addresses.

64. The method of claim 62, wherein said virtual source address corresponds to only a single client source address.

65. The method of claim 62, wherein said virtual destination address corresponds to a plurality of server destination addresses.

66. The method of claim 62, wherein said virtual destination address corresponds to only a single server destination address.

67. The method of claim 59, wherein said container packet is a globally routable IP based packet.

68. The method of claim 59, wherein the PAR transforming said second source and destination addresses to fourth source and destination addresses further comprises performing a lookup to determine said fourth source and destination addresses.

69. In a subscriber application routing apparatus (SAR), a method comprising:

receiving a packet from a client of an application service subscriber (Subscriber) to be delivered to an application service hosted by a server of an application service provider (Provider), said packet employing a first source and destination address pair having a first source address that identifies the client as the source of the packet and a first destination address identifying the SAR as an immediate intermediate recipient of the packet, with the first destination address further identifying the server of the Provider for the SAR;

transforming the packet for forwarding to said server, including transforming the first source and destination addresses to second source and destination addresses with the second source address identifying the SAR as the source of the packet and the second destination address identifying an application routing device of the Provider (PAR) as the recipient of the transformed packet, the second source address also identifying the client as the original source of the transformed packet and the second destination address also identifying the server as the ultimate destination of the transformed packet; and

embedding the transformed packet as a payload of a container packet and transmitting the container packet to the PAR to be subsequently extracted and forwarded to the server by the PAR, the container packet employing a third source and destination address pair identifying the SAR as the source of the container packet and the PAR as the destination of the container packet.

70. The method of claim 69, wherein the first destination address identifying the SAR as an immediate intermediate recipient of the packet is obtained from a domain name service.

71. The method of claim 69, wherein the SAR transforming the packet further comprises:

performing a lookup to identify the second source and destination addresses, said second source and destination addresses together representing a virtual private network tunnel provisioned between said SAR and PAR and associated with said application service.

72. The method of claim 69, wherein the second source and destination addresses represent a virtual address pair including a non-routable virtual source address and a non-routable virtual destination address.

73. The method of claim 69, wherein said container packet is a globally routable IP based packet.

74. An application routing apparatus (SAR) comprising:

a storage medium having stored therein a plurality of programming instructions, which when executed cause the apparatus to

receive a packet from a client of an application service subscriber (Subscriber) to be delivered to an application service hosted by a server of an application service provider (Provider), said packet employing a first source and destination address pair having a first source address that identifies the client as the source of the packet and a first destination address identifying the SAR as an immediate intermediate recipient of the packet, with the first destination address further identifying the server of the Provider for the SAR,

transform the packet for forwarding to said server, including instructions to transform the first source and destination addresses to second source and destination addresses with the second source address identifying the SAR as the source of the packet and the second destination address identifying the PAR as the recipient of the transformed packet, the second source address also identifying the client as the original source of the transformed packet and the second destination address also identifying the server as the ultimate destination of the transformed packet; and

embed the transformed packet as a payload of a container packet and transmit the container packet to the PAR to be subsequently extracted and forwarded to the server by the PAR, the container packet employing a third source and destination address pair identifying the SAR as the source of the container packet and the PAR as the destination of the container packet; and

an execution unit coupled to the storage medium for executing the plurality of programming instructions.

75. The apparatus of claim 74, wherein the first destination address identifying the SAR as an immediate intermediate recipient of the packet is obtained from a domain name service.

76. The apparatus of claim 74, wherein the SAR transforming the packet further comprises:

performing a lookup to identify the second source and destination addresses, said second source and destination addresses together representing a virtual private network tunnel provisioned between said SAR and PAR and associated with said application service.

77. The apparatus of claim 74, wherein the second source and destination addresses represent a virtual address pair including a non-routable virtual source address and a non-routable virtual destination address.

78. The apparatus of claim 74, wherein said container packet is a globally routable IP based packet.

79. In a provider application routing apparatus (PAR), a method comprising: receiving a container packet from an application routing apparatus of a Subscriber (SAR) to be delivered to an application service hosted by a server of the Provider, the container packet employing a first source and destination address pair with the first source address identifying the SAR as the source and the first destination address identifying the PAR as the recipient, and including an embedded packet having a transformed second source and destination address pair with the second source address identifying the SAR as the source of the packet and the second destination address identifying the PAR as the recipient of the transformed packet, the second source address also identifying a client of the Subscriber as the original source of the packet, and the second destination address also identifying the server as the ultimate destination of the transformed packet;

extracting the embedded payload and further transforming the extracted payload as a twice transformed packet, including transforming said second source and destination addresses to third source and destination addresses,

with the third source and destination addresses identifying the PAR and the server as the respective source and destination of the twice transformed packet, the third source address further identifying the client as the original source of the twice transformed packet; and

the PAR transmitting the twice transformed packet to the server.

80. The method of claim 79, wherein the second source and destination addresses represent a virtual address pair including a non-routable virtual source address and a non-routable virtual destination address.

81. The method of claim 79, wherein said container packet is a globally routable IP based packet.

82. The method of claim 79, wherein the PAR transforming said second source and destination addresses to fourth source and destination addresses further comprises performing a lookup to determine said fourth source and destination addresses.

83. A provider application routing apparatus (PAR) comprising:

a storage medium having stored therein a plurality of programming instructions, which when executed cause the apparatus to

In a provider application routing apparatus (PAR), a method comprising:

receive a container packet from an application routing apparatus of a Subscriber (SAR) to be delivered to an application service hosted by a server of the Provider, the container packet employing a first source and destination address pair with the first source address identifying the SAR as the source and the first destination address identifying the PAR as the recipient, and including an embedded packet having a transformed second source and destination address pair with the second source address identifying the SAR as the source of the packet and the second destination address identifying the PAR as the recipient of the transformed packet, the second source address also identifying a client of the Subscriber as the original source of the packet, and the second destination address also identifying the server as the ultimate destination of the transformed packet,

extract the embedded payload and further transform the extracted payload as a twice transformed packet, including transforming said second source and destination addresses to third source and destination addresses, with the third source and destination addresses identifying the PAR and the server as the respective source and destination of the twice transformed packet, the third source address further identifying the client as the original source of the twice transformed packet, and

transmit the twice transformed packet to the server; and

an execution unit coupled to the storage medium for executing the plurality of programming instructions.

84. The apparatus of claim 83, wherein the second source and destination addresses represent a virtual address pair including a non-routable virtual source address and a non-routable virtual destination address.

85. The apparatus of claim 83, wherein said container packet is a globally routable IP based packet.

86. The apparatus of claim 83, wherein the PAR transforming said second source and destination addresses to fourth source and destination addresses further comprises performing a lookup to determine said fourth source and destination addresses.

87. A method comprising:

a client of an application service subscriber (Subscriber) transmitting a packet to an application routing apparatus of the Subscriber (SAR), said packet to be delivered to an application service hosted by a server of an application service provider (Provider) and employing a first source and destination address pair having a first source address that identifies the client as the source of the packet and a first destination address identifying the application routing apparatus of the Subscriber as an immediate intermediate recipient of the packet, with the first destination address further identifying the server of the Provider; and

the SAR, in cooperation with an application routing apparatus of the Provider (PAR), delivering the packet to the server including successively transforming said first source and destination addresses to intermediate source



and destination addresses that facilitate routing of the packet, and at the same time maintaining implicit identification of the original source and ultimate destination of the packet.

88. The method of claim 87, wherein the intermediate second source and destination addresses represent a virtual address pair including a non-routable virtual source address and a non-routable virtual destination address.

89. The method of claim 87, wherein said non-routable virtual source address and said non-routable virtual destination address are wrapped in a globally routable IP based container packet.

90. In a SAR, a method comprising:

receiving a packet from a client of an application service subscriber (Subscriber) to be delivered to an application service hosted by a server of an application service provider (Provider), the packet having a first source and destination address pair having a first source address that identifies the client as the source of the packet and a first destination address identifying the SAR as an immediate intermediate recipient of the packet, with the first destination address further identifying the server of the Provider;

transforming the packet for forwarding to said server, including transforming the first source and destination addresses to second source and destination addresses with the second source address identifying the SAR as the source of the packet and the second destination address identifying an application routing device of the Provider (PAR) as the recipient of the transformed packet, the second source address also identifying the client as original source of the transformed packet and the second destination address also identifying the server as the ultimate destination of the transformed packet; and


delivering, in cooperation with a PAR, the packet to the server, wherein said delivering includes further transforming said second source and destination addresses to intermediate source and destination addresses that facilitate routing of the packet, and at the same time maintaining implicit identification of the original source and ultimate destination of the packet.

91. In a PAR, a method comprising:

receiving a container packet from an application routing apparatus of a Subscriber (SAR), said SAR forwarding an embedded packet on behalf of a client of the SAR to be delivered to an application service hosted by a server of an application service provider (Provider), the embedded packet having a first transformed source address that identifies the SAR as the intermediate source of the packet and the client as the original source of the packet, and a first transformed destination address identifying the PAR as an immediate intermediate recipient of the packet, with the first transformed destination address further identifying the server as the ultimate destination of the embedded packet;

extracting the embedded packet from the container packet;

transforming the packet for forwarding to said server, including transforming the first transformed source and destination addresses to second transformed source and destination addresses with the second transformed source address identifying the PAR as the source of the packet and the second transformed destination address identifying the server as the recipient of the transformed packet, the second transformed source address also identifying the client as the original source of the successively transformed packet; and transmitting the twice transformed packet to the server.



**FIG. 1**  
**(PRIOR ART)**




FIG. 2




FIG. 3A




FIG. 3B

▼ APPLICATIONS

Add Application

Manage Applications

401

▼ SUBSCRIBERS

Add Subscriber

Manage Subscribers

402

▼ SERVERS

Add Server

Manage Servers

403

▼ CONTRACTS

Add Contract

Manage Contracts

404

▼ ADD CONTRACT

Subscriber Name

Application Name

Server Name(s)

FUILLMENT OPTIONS

Encryption? ☒ None ☐ Blowfish ☐ 3DES

Compression?

Bandwidth throttling?

Ports to allow

Ports to monitor

406

CANCEL

RESET

ADD

FIG. 4




FIG. 5






FIG. 6




FIG. 7





FIG. 8A






FIG. 9

**THIS PAGE BLANK (USPTO)**

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
7 March 2002 (07.03.2002)

PCT

(10) International Publication Number  
**WO 02/019651 A3**

(51) International Patent Classification<sup>7</sup>: **H04L 29/06**,  
G06F 9/46, H04L 29/12

(21) International Application Number: PCT/US01/26456

(22) International Filing Date: 24 August 2001 (24.08.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/228,128 25 August 2000 (25.08.2000) US  
09/870,959 30 May 2001 (30.05.2001) US

(71) Applicant: **FLATROCK, INCORPORATED** [US/US];  
1505 S.E. Gideon, Suite 600, Portland, OR 97202 (US).

(72) Inventors: **BANKA, Peter, S.**; 7941 SE 36th, Portland,  
OR 97202 (US). **SILVERBERG, Sam, A.**; 5831 NE Stan-  
ton, Portland, OR 97213 (US).

(74) Agents: **KLINDTWORTH, Jason, K.** et al.; Columbia IP  
Law Group, PC, 4900 SW Meadows Road, Suite 109, Lake  
Oswego, OR 97035 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK,  
SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian  
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European  
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,  
IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,  
CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD,  
TG).

**Declarations under Rule 4.17:**


- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for all designations
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations

**Published:**

- with international search report

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR PROVIDING NETWORK DEPENDENT APPLICATION SERVICES



(57) Abstract: A method and apparatus for providing network dependent application services is provided. In accordance with one embodiment of the invention, a first group of one or more application service contracts specifying subscriptions to one or more application services are provided to a community of one or more subscriber application routers (SAR) by a first application service Provider. One or more application delivery transports are then automatically provisioned in accordance with the one or more application service contracts, and selected ones of the application services are delivered through selected ones of said application delivery transports.

WO 02/019651 A3



— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**(88) Date of publication of the international search report:**  
26 September 2002



## INTERNATIONAL SEARCH REPORT

International Application No.

S 01/26456

<b>A. CLASSIFICATION OF SUBJECT MATTER</b> IPC 7 H04L29/06 G06F9/46 H04L29/12		
According to International Patent Classification (IPC) or to both national classification and IPC		
<b>B. FIELDS SEARCHED</b> Minimum documentation searched (classification system followed by classification symbols) IPC 7 G06F H04L		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used) EPO-Internal, WPI Data, PAJ, IBM-TDB, INSPEC		
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 99 22332 A (INTERDESIGN HDL) 6 May 1999 (1999-05-06)	1,2,6,7, 11,12, 16,19, 23,24,28
Y	the whole document	3-5, 8-10, 13-15, 17,18, 20-22, 25-27, 29,30, 33-37, 40-44, 49-52, 57,58
---		
-/--		
<input checked="" type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex.		
<p>* Special categories of cited documents:</p> <p>*A* document defining the general state of the art which is not considered to be of particular relevance</p> <p>*E* earlier document but published on or after the international filing date</p> <p>*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>*O* document referring to an oral disclosure, use, exhibition or other means</p> <p>*P* document published prior to the international filing date but later than the priority date claimed</p> <p>*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>*8* document member of the same patent family</p>		
Date of the actual completion of the international search  2 July 2002		Date of mailing of the international search report  18. 07. 2002
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016		Authorized officer  Bertolissi, E

Form PCT/ISA/210 (second sheet) (July 1992)

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/US 01/26456

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5 953 229 A (CLARK STEVEN J ET AL) 14 September 1999 (1999-09-14)  abstract column 3, line 17 - line 65 ----	3-5, 8-10, 13-15, 17,18, 20-22, 25-27, 43,44, 49-52, 57,58
Y	US 5 774 668 A (CHOQUIER PHILIPPE ET AL) 30 June 1998 (1998-06-30)  abstract column 1, line 40 -column 3, line 52 column 10, line 20 - line 48 figures 1-5 ----	29,30, 33-37, 40-42
A	IONA TECHNOLOGIES: "OrbixNames Programmer's and Administrator's Guide" IONA TECHNOLOGIES MANUALS, June 1999 (1999-06), XP002178411 page 37 -page 48 ----	29-42
A	MICROSOFT CORPORATION: "DCOM Technical Overview" MICROSOFT CORPORATION DOCUMENTATION, November 1996 (1996-11), XP002178408 Security Load Balancing ----	29-42
A	GARFINKEL SIMSON; SPAFFORD GENE: "WEB SECURITY AND COMMERCE" June 1997 (1997-06) , O'REILLY XP002196011 page 99 -page 131 ----	1-58
A	YANG Z ET AL: "COBRA: A PLATFORM FOR DISTRIBUTED OBJECT COMPUTING" OPERATING SYSTEMS REVIEW (SIGOPS), ACM HEADQUARTER. NEW YORK, US, vol. 30, no. 2, 1 April 1996 (1996-04-01), pages 4-31, XP000585086 2 Overview of OMG OMA 3.9 Logacy systems Figure 5 ----- -/--	1-58

## INTERNATIONAL SEARCH REPORT

International Application No.  
PCT/95/01/26456

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	<p>RUDOLF SCHREINER: "Corba Firewalls" OBJECTSECURITY WHITEPAPER, 'Online! 15 August 1999 (1999-08-15), XP002204213 Retrieved from the Internet: &lt;URL:http://www.objectsecurity.com/whitepapers/corba/fw/main.html&gt; 'retrieved on 2002-07-01! (3). The OMG proposal (4). Other techniques ---</p>	59-91
Y	<p>P. SRISURESH: "RFC 2709 - Security Model with Tunnel-mode IPsec for NAT Domains" REQUEST FOR COMMENTS, 'Online! XP002204214 Retrieved from the Internet: &lt;URL:http://www.ietf.org/rfc/rfc2709.txt&gt; 'retrieved on 2002-07-01! Abstract 3. Security model of IPC-NAT ---</p>	59-91
Y	<p>D. INGHAM, O. REES, A. NORMAN: "HPL-1999-50 - CORBA Transactions Through Firewalls" HEWLETT PACKARD TECHNICAL REPORT, 'Online! XP002204215 Retrieved from the Internet: &lt;URL:http://www.hpl.hp.com/techreports/1999/HPL-1999-50.html&gt; 'retrieved on 2002-07-01! Abstract Firewalls and CORBA Related Work The CORBAGate Object gateway Design Goals Object Gateway Structure ---</p>	59-91
Y	<p>P. SRISURESH, M. HOLDREGE: "RFC 2663 - IP Network Address Translator (NAT) Terminology and Considerations" REQUEST FOR COMMENTS, 'Online! XP002204216 Retrieved from the Internet: &lt;URL:http://www.ietf.org/rfc/rfc2663.txt&gt; 'retrieved on 2002-07-01! Abstract 4.3. Twice NAT 6.0. Private networks and tunnels - 6.2. Backbone partitioned private networks ---</p>	59-91
	-/--	

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 01/26456

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>NORIFUSA M: "Internet security: difficulties and solutions"  INTERNATIONAL JOURNAL OF MEDICAL INFORMATICS, ELSEVIER SCIENTIFIC PUBLISHERS, SHANNON, IR,  vol. 49, no. 1, March 1998 (1998-03),  pages 69-74, XP004149463  ISSN: 1386-5056  Abstract  4. The VPN solution - 7. Examples  Fig. 2</p>	59-91
A	<p>US 5 862 328 A (COLYER ADRIAN MARK)  19 January 1999 (1999-01-19)  abstract  column 5, line 20 -column 6, line 29  column 8, line 23 - line 41</p>	59-91
A	<p>"PROGRAM FOR EXPORTING TRANSMISSION CONTROL PROTOCOL-BASED SERVICES THROUGH FIREWALLS"  IBM TECHNICAL DISCLOSURE BULLETIN, IBM CORP. NEW YORK, US,  vol. 40, no. 12,  1 December 1997 (1997-12-01), pages 161-162, XP000754125  ISSN: 0018-8689  the whole document</p>	59-91
A	<p>US 6 055 236 A (BORELLA MICHAEL S ET AL)  25 April 2000 (2000-04-25)  abstract  column 5, line 1 - line 63</p>	59-91

# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US 01/26456

## Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:  
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:  
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:  
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

## Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☒ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☒ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/SA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1-58

Method, devices and apparatuses for providing application service contracts

2. Claims: 59-91

Method, and apparatuses for transforming packets

## INTERNATIONAL SEARCH REPORT

International Application No  
US 01/26456

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
WO 9922332	A	06-05-1999	AU	1199199 A	17-05-1999
			WO	9922332 A1	06-05-1999
US 5953229	A	14-09-1999	AU	4491297 A	17-04-1998
			EP	1008043 A1	14-06-2000
			WO	9813757 A1	02-04-1998
US 5774668	A	30-06-1998	US	5951694 A	14-09-1999
US 5862328	A	19-01-1999	GB	2305270 A	02-04-1997
			DE	69606184 D1	17-02-2000
			DE	69606184 T2	13-07-2000
			EP	0850446 A1	01-07-1998
			WO	9710546 A1	20-03-1997
			JP	10511794 T	10-11-1998
US 6055236	A	25-04-2000	US	6353614 B1	05-03-2002



**THIS PAGE BLANK (USPTO)**